


Two-stage Permanent Magnet Variable Speed Screw Compressor



Technical parameters of Two-stage Permanent Magnet Variable Speed Screw Compressor

Model	Motor (KW)	Capacity / Pressure (m³/min/Bar)		Dimension (L×W×H)mm	Pipe	Weight (kg)
DH-22TPM	22	4.2/8	3.5/10	1200*850*1100	G1	600
DH-30TPM	30	6.1/8	4.2/10	1500*950*1225	G1 1/2	800
DH-37TPM	37	7.5/8	6.1/10	1500*950*1225	G1 1/2	900
DH-45TPM	45	9.6/8	7.5/10	1650*1170*1440	G2*	1200
DH-55TPM	55	12.5/8	9.6/10	2000*1350*1600	DN50	1500
DH-75TPM	75	15.5/8	12.5/10	2000*1350*1600	DN50	1600
DH-90TPM	90	19.8/8	15/10	2400*1550*1800	DN65	2200
DH-110TPM	110	22.8/8	19/10	2400*1550*1800	DN65	2300
DH-132TPM	132	27/8	22.6/10	2730*1710*1950	DN80	3200
DH-160TPM	160	32/8	27/10	2730*1710*1950	DN80	3500
DH-185TPM	185	37.8/8	31/10	3500*2150*2100	DN100	4800
DH-200TPM	200	42.5/8	37/10	3500*2150*2100	DN100	4900
DH-220TPM	220	46/8	41/10	3500*2150*2100	DN100	5200
DH-250TPM	250	51/8	45/10	3500*2150*2100	DN100	5500
DH-280TPM	280	57/8	49/10	3800*2300*2300	DN125	6700
DH-315TPM	315	62/8	51/10	3800*2300*2300	DN125	7000
DH-355TPM	355	69.2/8	54.2/10	3800*2300*2300	DN125	8500

*Specifications are subject to change without notice.